

## HVM HAND LEVER VALVE



The direction-change turns with good hand feeling and exact orientation

Large effective circulating area leads to little pressure loss

Panel and body installation are optional. The panel installation can be attached with installing nut

### TECHNICAL DATA

Model	HVM4□□□-08	HVM4□□□-10	HVM4□□□-15
<b>Operating medium</b>	Air filtered by 40um filter element		
<b>Version</b>	Manual control direct acting type		
<b>Pneumatic connection</b>	PT1/4"	PT3/8"	PT1/2"
<b>Orifice size</b>	88mm <sup>2</sup> (Cv=4.89)		
<b>Valve type</b>	4 port 2 position, 4 port 3 position		
<b>Lubrication</b>	Not required		
<b>Operating pressure</b>	0-1.0Mpa		
<b>Proof pressure</b>	1.5Mpa		
<b>Operating temperature</b>	-20-70°C		
<b>Operating angle</b>	90° (4/3 port:45°)		



1 bar=0.1MPa=14.5PSI

**KEY CODE**

**HVM - 4 - 30 - C - 15**

HVM	4	30	C	15	
SERIES	TYPE	VALVE TYPE	VALVE TYPE	SERIES	PORT SIZE
HVM hand lever valve	4:400 series	10:4 port 2 position	C:Center closed	HVM400	08:1/4"
		30:4 port 3 position	E:Center exhaust		10:3/8"
			P:Center pressure		15:1/2"

For further information, please consult with us.

**DIMENSIONS**

**Model: HVM430C-15**

