

HVT HAND LEVER VALVE



The direction-change turns with good hand feeling and exact orientation

Large effective circulating area leads to little pressure loss

TECHNICAL DATA

Model	HVT□□□-06	HVT□□□-08
Operating medium	Air filtered by 40um filter element	
Version	Manual control direct acting type	
Pneumatic connection	PT1/8"	PT1/4"
Orifice size	14mm ² (Cv=0.78)	16mm ² (Cv=0.89)
Valve type	4 port 2 position, 4 port 3 position	
Lubrication	Not required	
Operating pressure	0-1.0Mpa	
Proof pressure	1.5Mpa	
Operating temperature	-20-70°C	
Operating angle	90° (4/3 port:45°)	



1 bar=0.1MPa=14.5PSI

KEY CODE

HVT - 2 - 30 - C - 06

HVT	2	30	C	06	
SERIES	TYPE	VALVE TYPE	VALVE TYPE	SERIES	PORT SIZE
HVT hand lever valve	2:200 SERIES	10:4 port 2 position	C:Center closed	HVT200	06:1/8"
		30:4 port 3 position	E:Center exhaust P:Center pressure	HVT300	08:1/4" 10:3/8"

For further information, please consult with us.

DIMENSIONS

Model: HVT230C-08

